

Day/night - varifocal - waterproof - 700TVL

Easy installation and setup



Reference: Cam700VF

Price: 459,80€

Description:

Features:

Weatherproof IR Camera SONY / SHARP Color CCD 42 pcs - 5mm IR-LED, IR Range 35M OSD/2D-DNR/BLC/MD/Privacy Masking 3-Axis Bracket, Hidden Cable Design Built-in 4 - 9 mm Manual Zoom Lens

Specifications:

Image Sensor: 1/3" Exview HAD CCD II (ICX672/3AKA) Color Mode: 650TVL; B/W Mode: 700TVL

Picture Elements:

PAL: 976(H) × 582(V)

NTSC: 976(H) × 494(V) Min. Illumination: 0.001 Lux (F2.0) / 0 Lux IR On TV System: PAL / NTSC Lens

Furnished: 4--9 mm Manual Zoom Lens (Optional 2.8--12mm Manual Zoom Lens) Infrared Luminary: 42

pieces - 5 mm IR-LED Illuminate Distance: 35 M Wavelength: 850 nm Waterproofing Criterion: IP 66 S/N

Ratio: More than 52dB Electronic Shutter: NTSC: 1/60~1/100,000, PAL: 1/50~1/110,000 Gamma: 0.45

Exposure: Auto Backlight: OFF/ON/BLC/HLC Pict Adjust: Mirror/Brightness/Contrast/Sharpness/Hue/Gain

ATR: ON/OFF Motion Det: OFF/ON (Detect sense/ Area Sel) Privacy Masking: OFF/ON (4 Zone)

Day/Night: True Day and Night (Auto/ Day / Night / Ext. D&N) 2D-NR: OFF/ON (Y/C level) Camera ID:

OFF/ON Sync. System: Internal White Balance: ATW / User1/User2 Gain Control: Auto Sync. System:

Internal Video Output: 1 Vp-p / 75 Ohms Power Supply: DC12V±10% Operation Temperature: -10°~

+50°RH95% Max Dimensions: 83x159mm With Bracket: 230(L)x86(W)x83(H)

[Link to the product](#)