

Telaccess 1B 1PB - Antivandal - Industrial quality

Telaccess version spéciale appel de rue avec GSM



Manufacturer: Telaccess

Reference: Telaccess SP GSM

Description:

[? PDF documentation link](#)

Specifications

Embedded mounting

Front plate in aluminium 4mm

Indoor & outdoor installation

Security screws

PABX and public Telecom line connection

Volume control – emission and reception

Very powerful emission level

Anti-vandal call buttons

Automatic call management (DSP)

Call monitoring – enabled / disabled

2 relays with programmable DTMF codes and duration

Latch mode possibility on relay 2 (video server or light control)

Building protection capabilities

Relay command with external contact (exit button)
Remote access and programming with DTMF codes
Privacy listening
Day/night mode selection with different process
Hands-free mode
Push button(s) enabled/disabled
Programmable minimum press duration on button(s)
Wait for answer programmable per called number
End of communication after relay activity
End of communication on no activity delay
Communication limited / unlimited
Alarm detection + number to call in case of alarm
Voice detection sensitivity
4 called numbers on no reply or busy for first button
2 called numbers on no reply or busy for next button(s)
End of call enabled / disabled by second press on button
Telecom norms CTR 21
CE agreement
Relay timers from 1~300 seconds
Relays contact rating 2A / 12VDC
Relays contact NO and NC
Power supply 12 VDC 1000 mA

Options

Rain cover for wall mounting
1 to 72 push buttons
Voice guidance 10 messages
Integrated badge reader (tot 748 badges)
Integrated camera
LCD backlight screen 2 lines
Remote control with Windows interface
IP 65 rain protection
IP video server

Dimensions

On the wall with Rain cover : 284 x 124 x 92 / 65 mm

In the wall, hHole dimensions : 260 x 110 x 50 mm

Front plate dimensions : 280 x 120 x 4 mm

[Link to the product](#)