

**Kit for integration MREM 76 - Delivered with antenna AEM 12, 10 badges and a Dinrail power supply 12 VDC**

Included : 1 reader MREM 76 + 1 antenna AEM 12, 1 power supply en 10 badges



**Manufacturer:** Techfass

**Reference:**Kit MREM 76/10

**Price:** 653,40€

**Options:**

:  
:  
:

**Description:**

**Badge reader with external antenna MREM 76-EM**

Reader module 125 kHz (TF/EM/HID Proximity) with integrated door controller can be installed wherever using a standard module is inappropriate for mechanical or security reasons.

All-purpose conception of the module enables installation in most of the electrical devices' cover designs thus adjusting the appearance of the reader modules to required look. Remote relay module WIO 22 can be used for increased security.

**Technical features**

Operating voltage 9 ÷ 15 V DC

Current consumption 95 mA, max. 130 mA ID technology 125 kHz (TF / EM / HID Prox)

Typical reading range 6 / 4 cm (with ISO card) Card memory 748 users + 2 master cards 748

Events memory - 2,000 -

Time schedules 64 per day of the week and for holidays + never / always

Real-time clock Available, with min. 12 hrs backup

Inputs 1x door contact, 1x REX 2x input

Outputs, indicators 1x relay NC/NO, 2A/24V, 1x transistor output 5V/5mA, 3x LED, 1x PIEZO buzzer

Communication interface RS 485 Optional data output Wiegand (configurable)

Tamper protection Opto-electronic Weight 0.084 kg (xREM 56), 0.034 kg (xREM 56E)

Operating environment Indoor, -20°C ? +40°C, humidity max. 75% non-condensing

Dimensions MREM 76 – Plastic installation box (81x81x25mm)

[Link to the product](#)