Uni IP SIP - 1 button - PoE

1 button, 1 relay, flush mounting. Look at the option for wall mounting.



Manufacturer: 2N Helios IP
Reference:H9153101

Price: 486,42€

Description:

Click here for the PDF documentation in English

Type : Helios IP SIP

Power supply : PoE or 12VDC
Number of button : 1
Button type : backlit
Loudspeaker type : 1 watt
Loudspeaker material: Mylar
Microphone : electred, omnidirectional

System installation : flush mounting
Mounting options :
On the wall with the roof option

Frontplate : metal
Box : plastic
External dimensions : 193 x 115 x 57mm max. (H x l x d)

Connections
A.
Using the LAN, without any additonal material, setup in point-to-point to one SIP phone, no IPBX needed.

The calling mode is unicast with transfer to another possible in case of timeout.

B.
iPBX managing codec G711 in alaw or µlaw for the audio. A group call is of course possible.

Setup of all parameters through a very userfriendly webserver.

The internal post to call can be a physical number or an IP SIP address.

3 numbers or IP SIP addresses per button (with timeout mode).
Max. duration of the call : timeout or EOC detection.

Relay : 1 installed on the PCB
Relay connection : NO/NC
Max. current : 1A/30 VDC/AC
Relay control : DTMF, SIP or RTP

Max. digits relay activation code : 4

Loudspeaker and microphone volume adjustable : yes, webserver parameter

Temperature limits: from -20°c up to +50°c

Link to the product