

Reader MREM 76E-EM - 748 users - 64 plannings - 4.700 events - Flush mounting

The reader module is designed for installation into round installation boxes with inner diameter 68 mm. This reader module is supplied with KU 68 installation box.



Manufacturer: Techfass

Reference: MREM 76E-EM

Price: 468,27€

Description:

The **MREM 76E-EM** reader modules (125 kHz readers with an embedded single door controller) are designed for connection to the RS 485 bus of the APS mini Plus access control system, or for standalone operation. It is possible to connect up to 32 reader modules to a single line of the APS mini Plus system. In effect the number of lines is not limited.

The reader module is designed for installation into round installation boxes with inner diameter 68 mm.

Mechanical design Weight 0.018 kg **Operating temperature** -10°C ÷ +40°C **Humidity** Max. 75%, non-condensing **Housing** Acc. to used installation components **Dimensions** Suited for mounting in round ? 68 mm boxes

Technical features Supply voltage 8 ÷ 15 VDC Current demand Typical 95 mA Maximal 130 mA Keypad N / A Operating frequency 125 kHz ID technology, typical reading range TF media 6 cm (with ISO card) EM Marin 6 cm (with ISO card) HID Prox 4 cm (with ISO card) Prastel 6 cm (with ISO card) Real time clock Yes, with self backup for 12 hrs. Memory ID media 748 ID, 2 master cards Events 4,700 Time schedules 64 Inputs Door status Logical potential-free contact Exit button / Handle Logical potential-free contact Outputs Door lock Relay NC/NO, 2A/24V Alarm Transistor output 5V/5mA Indicators 3x LED 1x PIEZO buzzer Tamper protection Opto-electronic Communication interface RS 485 for system BUS Addresses used at system BUS 1 address HW address setting type Address jumpers External device interface 1x WIEGAND input / output 1x I/O port - ext. tamper / ext. reader buzzer control Alternative data output WIEGAND (configurable)

[Leaflet xREM 76E](#)

[Link to the product](#)