

**Telaccess 1C - Robust keycode - Antivandalism - Industrial quality**

Industrial keypad - Designed for heavy work



**Manufacturer: Telaccess**

**Reference: T1C**

**Price: 1.141,03€**

**Description:**

[PDF documentation link](#)

Specifications

- Embedded mounting
- Front plate in aluminium 4mm
- Indoor & outdoor installation
- Security screws
- PABX and public Telecom line connection
- Volume control – emission and reception
- Very powerful emission level
- Anti-vandal call buttons
- Automatic call management (DSP)
- Call monitoring – enabled / disabled
- 2 relays with programmable DTMF codes and duration
- Latch mode possibility on relay 2 (video server or light control)
- Building protection capabilities

Relay command with external contact (exit button)  
Remote access and programming with DTMF codes  
Privacy listening  
Day/night mode selection with different process  
Hands-free mode  
Push button(s) enabled/disabled  
Programmable minimum press duration on button(s)  
Wait for answer programmable  
End of communication after relay activity  
End of communication on no activity delay  
Communication limited / unlimited  
Alarm detection + number to call in case of alarm  
Voice detection sensitivity  
4 called numbers on no reply or busy for main button  
2 called numbers on no reply or busy for short numbers  
End of call enabled / disabled by second press on button  
Telecom norms CTR 21  
CE agreement  
Relay timers from 1~300 seconds  
Relays contact rating 2A / 12VDC  
Relays contact NO and NC  
Power supply 12 VDC 1000 mA

## Dimensions

On the wall

Rain cover : 284 x 124 x 92 / 65 mm

In the wall

Hole dimensions : 260 x 110 x 52 mm

Front plate dimensions : 280 x 120 x 4 mm

## Options

Rain cover for wall mounting

Voice guidance 10 messages

Integrated badge reader (748 badges) standalone or networked

Integrated camera (Telaccess 1C only)

Remote control with Windows interface

IP 65 rain protection

IP video server

[Link to the product](#)