

Uni IP SIP - 2 buttons - PoE

2 buttons, 1 relay, flush mounting. Look at the option for wall mounting.



Manufacturer: 2N Helios IP

Reference: H9153102

Price: 513,04€

Description:



[Click here for the PDF documentation in English](#)

Type : UNI IP SIP 2 buttons

Power supply : PoE or 12VDC

Number of button : 2

Buttons type : backlit

Loudspeaker type : 1 watt

Loudspeaker material: Mylar

Microphone : electret, omnidirectional

System installation : flush mounting

Mounting options :

On the wall with the roof option

Frontplate : metal

Box : plastic

External dimensions : 193 x 115 x 57mm max. (H x l x d)

Connections

A.

Using the LAN, without any additional material, setup in point-to-point to one SIP phone, no IPBX needed.

The calling mode is unicast with transfer to another possible in case of timeout.

B.

iPBX managing codec G711 in alaw or μ law for the audio. A group call is of course possible.

Setup of all parameters through a very userfriendly webserver.

The internal post to call can be a physical number or an IP SIP address.

3 numbers or IP SIP addresses per button (with timeout mode).

Max. duration of the call : timeout or EOC detection.

Relay : 1 installed on the PCB

Relay connection : NO/NC

Max. current : 1A/30 VDC/AC

Relay control : DTMF, SIP or RTP

Max. digits relay activation code : 4

Loudspeaker and microphone volume adjustable : yes, webserver parameter

Temperature limits: from -20°C up to +50°C

[Link to the product](#)